



Micro Commercial Components
21201 Itasca Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

SA5.0(C)(A) THRU SA170(C)(A)

Features

- Glass passivated chip
- Low leakage
- Uni and Bidirectional unit
- Excellent clamping capability
- the plastic material has U/L recognition 94V-O
- Fast response time

MECHANICAL DATA

Case: Molded Plastic

Marking: Unidirectional-type number and cathode band
Bidirectional-type number only

Weight: 0.4 grams

Maximum Ratings


- Operating Temperature: -65°C to $+175^{\circ}\text{C}$
- Storage Temperature: -65°C to $+175^{\circ}\text{C}$
- For capacitive load, derate current by 20%

Electrical Characteristics @ 25°C Unless Otherwise Specified

Peak Power Dissipation	P_{PK}	500W	$T_A=25^{\circ}\text{C}$
Peak Forward Surge Current	I_{FSM}	70A	8.3ms, half sine
Steady State Power Dissipation	$P_{M(AV)}$	1.0W	$T_J=75^{\circ}\text{C}$

**500WATTS TRANSIENT
VOLTAGE SUPPRESSOR
5.0 TO 170 VOLTS**

DO-15



DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	0.230	0.300	5.80	7.60	
B	0.104	0.140	2.60	3.60	
C	0.026	0.034	0.71	0.86	
D	1.000	-----	25.40	-----	

RATING AND CHARACTERISTIC CURVES SA5.0 THRU SA170CA




Fig. 1-PEAK PULSE POWER RATING CURVE




Fig. 2-PULSE DERATING CURVE




Fig. 3-PULSE WAVEFORM




Fig. 4-TYPICAL JUNCTION CAPACITANCE

UNIDIRECTIONAL




Fig. 5-STEADY STATE POWER DERATING CURVE




Fig. 6-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT UNIDIRECTIONAL ONLY

UNI-DIRECTIONAL 500 Watt Axial Lead TVS

UNI-DIRECTIONAL PART NUMBER	REVERSE STAND-OFF VOLTAGE VRWM (V)	BREAKDOWN VOLTAGE VBR (V) MIN. @IT	BREAKDOWN VOLTAGE VBR (V) MAX. @IT	TEST CURRENT IT (mA)	MAXIMUM CLAMPING VOLTAGE @I _{PP} VC (V)	PEAK PULSE CURRENT I _{PP} (A)	REVERSE LEAKAGE @VRWM IR (uA)
SA5.0	5.00	6.40	7.30	10	9.6	52.3	600
SA5.0A	5.00	6.40	7.00	10	9.2	54.3	600
SA6.0	6.00	6.67	8.15	10	11.4	43.9	600
SA6.0A	6.00	6.67	7.37	10	10.3	48.5	600
SA6.5	6.50	7.22	8.82	10	12.3	40.7	400
SA6.5A	6.50	7.22	7.98	10	11.2	44.7	400
SA7.0	7.00	7.78	9.51	10	13.3	37.8	150
SA7.0A	7.00	7.78	8.60	10	12.0	41.7	150
SA7.5	7.50	8.33	10.20	1	14.3	35.0	50
SA7.5A	7.50	8.33	9.21	1	12.9	38.8	50
SA8.0	8.00	8.89	10.90	1	15.0	33.3	25
SA8.0A	8.00	8.89	9.83	1	13.6	36.7	25
SA8.5	8.50	9.44	11.50	1	15.9	31.4	10
SA8.5A	8.50	9.44	10.40	1	14.4	34.7	10
SA9.0	9.00	10.00	12.20	1	16.9	29.5	5
SA9.0A	9.00	10.00	11.10	1	15.4	32.5	5
SA10	10.00	11.10	13.60	1	18.8	26.6	3
SA10A	10.00	11.10	12.30	1	17.0	29.4	3
SA11	11.00	12.20	14.90	1	20.1	24.9	3
SA11A	11.00	12.20	13.50	1	18.2	27.4	3
SA12	12.00	13.30	16.30	1	22.0	22.7	3
SA12A	12.00	13.30	14.70	1	19.9	25.1	3
SA13	13.00	14.40	17.60	1	23.8	21.0	3
SA13A	13.00	14.40	15.90	1	21.5	23.2	3
SA14	14.00	15.60	19.10	1	25.8	19.4	3
SA14A	14.00	15.60	17.20	1	23.2	21.5	3
SA15	15.00	16.70	20.40	1	26.9	18.8	3
SA15A	16.00	16.70	18.50	1	24.4	20.6	3
SA16	16.00	17.80	21.80	1	28.8	17.6	3
SA16A	16.00	17.80	19.70	1	26.0	19.2	3
SA17	17.00	18.90	23.10	1	30.5	16.4	3
SA17A	17.00	18.90	20.90	1	27.6	16.1	3
SA18	18.00	20.00	24.40	1	32.2	15.5	3
SA18A	18.00	20.00	22.10	1	29.2	17.2	3
SA20	20.00	22.20	27.10	1	35.8	13.9	3
SA20A	20.00	22.20	24.50	1	32.4	15.4	3
SA22	22.00	24.40	29.80	1	39.4	12.7	3
SA22A	22.00	24.40	26.90	1	35.5	14.1	3
SA24	24.00	26.70	32.60	1	43.0	11.6	3
SA24A	24.00	26.70	29.50	1	38.9	12.8	3
SA26	26.00	28.90	35.30	1	46.6	10.7	3
SA26A	26.00	28.90	31.90	1	42.1	11.9	3
SA28	28.00	31.10	38.00	1	50.0	9.9	3
SA28A	28.00	31.10	34.40	1	45.4	11.0	3
SA30	30.00	33.30	40.70	1	53.5	9.3	3
SA30A	30.00	33.30	36.80	1	48.4	10.3	3
SA33	33.00	36.70	44.90	1	59.0	8.5	3
SA33A	33.00	36.70	40.60	1	53.3	9.4	3
SA36	36.00	40.00	48.90	1	64.3	7.8	3
SA36A	36.00	40.00	44.20	1	58.1	8.6	3
SA40	40.00	44.40	54.30	1	71.4	7.0	3
SA40A	40.00	44.40	49.10	1	64.5	7.8	3
SA43	43.00	47.80	58.40	1	76.7	6.5	3
SA43A	43.00	47.80	52.80	1	69.4	7.2	3
SA45	45.00	50.00	61.10	1	80.3	6.2	3
SA45A	45.00	50.00	55.30	1	72.7	6.9	3
SA48	48.00	53.30	65.10	1	85.5	5.8	3
SA48A	48.00	53.30	58.90	1	77.4	6.5	3
SA51	51.00	56.70	69.30	1	91.1	5.5	3
SA51A	51.00	56.70	62.70	1	82.4	6.1	3
SA54	54.00	60.00	73.30	1	96.3	5.2	3
SA54A	54.00	60.00	66.30	1	87.1	5.7	3
SA58	58.00	64.40	78.70	1	103.0	4.9	3
SA58A	58.00	64.40	71.20	1	93.6	5.3	3
SA60	60.00	66.70	81.50	1	107.0	4.7	3
SA60A	60.00	66.70	73.70	1	96.8	5.2	3
SA64	64.00	71.10	86.90	1	114.0	4.4	3
SA64A	64.00	71.10	78.60	1	103.0	4.9	3

UNI-DIRECTIONAL 500 Watt Axial Lead TVS

UNI-DIRECTIONAL PART NUMBER	REVERSE STAND-OFF VOLTAGE VRWM (V)	BREAKDOWN VOLTAGE VBR (V) MIN. @IT	BREAKDOWN VOLTAGE VBR (V) MAX. @IT	TEST CURRENT IT (mA)	MAXIMUM CLAMPING VOLTAGE @I _{PP} VC (V)	PEAK PULSE CURRENT I _{PP} (A)	REVERSE LEAKAGE @VRWM IR (uA)
SA70	70.00	77.80	95.10	1	125.0	4.0	3
SA70A	70.00	77.80	86.00	1	113.0	4.4	3
SA75	75.00	83.30	102.00	1	134.0	3.7	3
SA75A	75.00	83.30	92.10	1	121.0	4.1	3
SA78	78.00	86.70	106.00	1	139.0	3.6	3
SA78A	78.00	86.70	95.80	1	126.0	4.0	3
SA85	85.00	94.40	115.00	1	151.0	3.3	3
SA85A	85.00	94.40	104.00	1	137.0	3.6	3
SA90	90.00	100.00	122.00	1	160.0	3.1	3
SA90A	90.00	100.00	111.00	1	146.0	3.4	3
SA100	100.00	111.00	136.00	1	179.0	2.8	3
SA100A	100.00	111.00	123.00	1	162.0	3.1	3
SA110	110.00	122.00	149.00	1	196.0	2.6	3
SA110A	110.00	122.00	135.00	1	177.0	2.8	3
SA120	120.00	133.00	163.00	1	214.0	2.3	3
SA120A	120.00	133.00	147.00	1	193.0	2.0	3
SA130	130.00	144.00	176.00	1	231.0	2.2	3
SA130A	130.00	144.00	159.00	1	209.0	2.4	3
SA150	150.00	167.00	204.00	1	269.0	1.9	3
SA150A	150.00	167.00	185.00	1	243.0	2.1	3
SA160	160.00	178.00	218.00	1	287.0	1.7	3
SA160A	160.00	178.00	197.00	1	259.0	1.9	3
SA170	170.00	189.00	231.00	1	304.0	1.6	3
SA170A	170.00	189.00	209.00	1	275.0	1.8	3

BI-DIRECTIONAL 500 Watt Axial Lead TVS

BI-DIRECTIONAL PART NUMBER	REVERSE STAND-OFF VOLTAGE VRWM (V)	BREAKDOWN VOLTAGE VBR (V) MIN. @IT	BREAKDOWN VOLTAGE VBR (V) MAX. @IT	TEST CURRENT IT (mA)	MAXIMUM CLAMPING VOLTAGE @I _{PP} VC (V)	PEAK PULSE CURRENT I _{PP} (A)	REVERSE LEAKAGE @VRWM IR (uA)
SA5.0C	5.00	6.40	7.30	10	9.6	52.3	1200
SA5.0CA	5.00	6.40	7.00	10	9.2	54.3	1200
SA6.0C	6.00	6.67	8.15	10	11.4	43.9	1200
SA6.0CA	6.00	6.67	7.37	10	10.3	48.5	1200
SA6.5C	6.50	7.22	8.82	10	12.3	40.7	800
SA6.5CA	6.50	7.22	7.98	10	11.2	44.7	800
SA7.0C	7.00	7.78	9.51	10	13.3	37.8	300
SA7.0CA	7.00	7.78	8.60	10	12.0	41.7	300
SA7.5C	7.50	8.33	10.20	1	14.3	35.0	100
SA7.5CA	7.50	8.33	9.21	1	12.9	38.8	100
SA8.0C	8.00	8.89	10.90	1	15.0	33.3	50
SA8.0CA	8.00	8.89	9.83	1	13.6	36.7	50
SA8.5C	8.50	9.44	11.50	1	15.9	31.4	20
SA8.5CA	8.50	9.44	10.40	1	14.4	34.7	20
SA9.0C	9.00	10.00	12.20	1	16.9	29.5	5
SA9.0CA	9.00	10.00	11.10	1	15.4	32.5	5
SA10C	10.00	11.10	13.60	1	18.8	26.6	3
SA10CA	10.00	11.10	12.30	1	17.0	29.4	3
SA11C	11.00	12.20	14.90	1	20.1	24.9	3
SA11CA	11.00	12.20	13.50	1	18.2	27.4	3
SA12C	12.00	13.30	16.30	1	22.0	22.7	3
SA12CA	12.00	13.30	14.70	1	19.9	25.1	3
SA13C	13.00	14.40	17.60	1	23.8	21.0	3
SA13CA	13.00	14.40	15.90	1	21.5	23.2	3
SA14C	14.00	15.60	19.10	1	25.8	19.4	3
SA14CA	14.00	15.60	17.20	1	23.2	21.5	3
SA15C	15.00	16.70	20.40	1	26.9	18.8	3
SA15CA	16.00	16.70	18.50	1	24.4	20.6	3
SA16C	16.00	17.80	21.80	1	28.8	17.6	3
SA16CA	16.00	17.80	19.70	1	26.0	19.2	3
SA17C	17.00	18.90	23.10	1	30.5	16.4	3
SA17CA	17.00	18.90	20.90	1	27.6	16.1	3
SA18C	18.00	20.00	24.40	1	32.2	15.5	3
SA18CA	18.00	20.00	22.10	1	29.2	17.2	3
SA20C	20.00	22.20	27.10	1	35.8	13.9	3
SA20CA	20.00	22.20	24.50	1	32.4	15.4	3
SA22C	22.00	24.40	29.80	1	39.4	12.7	3
SA22CA	22.00	24.40	26.90	1	35.5	14.1	3
SA24C	24.00	26.70	32.60	1	43.0	11.6	3
SA24CA	24.00	26.70	29.50	1	38.9	12.8	3
SA26C	26.00	28.90	35.30	1	46.6	10.7	3
SA26CA	26.00	28.90	31.90	1	42.1	11.9	3
SA28C	28.00	31.10	38.00	1	50.0	9.9	3
SA28CA	28.00	31.10	34.40	1	45.4	11.0	3
SA30C	30.00	33.30	40.70	1	53.5	9.3	3
SA30CA	30.00	33.30	36.80	1	48.4	10.3	3
SA33C	33.00	36.70	44.90	1	59.0	8.5	3
SA33CA	33.00	36.70	40.60	1	53.3	9.4	3
SA36C	36.00	40.00	48.90	1	64.3	7.8	3
SA36CA	36.00	40.00	44.20	1	58.1	8.6	3
SA40C	40.00	44.40	54.30	1	71.4	7.0	3
SA40CA	40.00	44.40	49.10	1	64.5	7.8	3
SA43C	43.00	47.80	58.40	1	76.7	6.5	3
SA43CA	43.00	47.80	52.80	1	69.4	7.2	3
SA45C	45.00	50.00	61.10	1	80.3	6.2	3
SA45CA	45.00	50.00	55.30	1	72.7	6.9	3
SA48C	48.00	53.30	65.10	1	85.5	5.8	3
SA48CA	48.00	53.30	58.90	1	77.4	6.5	3
SA51C	51.00	56.70	69.30	1	91.1	5.5	3
SA51CA	51.00	56.70	62.70	1	82.4	6.1	3
SA54C	54.00	60.00	73.30	1	96.3	5.2	3
SA54CA	54.00	60.00	66.30	1	87.1	5.7	3
SA58C	58.00	64.40	78.70	1	103.0	4.9	3
SA58CA	58.00	64.40	71.20	1	93.6	5.3	3
SA60C	60.00	66.70	81.50	1	107.0	4.7	3
SA60CA	60.00	66.70	73.70	1	96.8	5.2	3
SA64C	64.00	71.10	86.90	1	114.0	4.4	3
SA64CA	64.00	71.10	78.60	1	103.0	4.9	3

BI-DIRECTIONAL 500 Watt Axial Lead TVS

BI-DIRECTIONAL PART NUMBER	REVERSE STAND-OFF VOLTAGE VRWM (V)	BREAKDOWN VOLTAGE VBR (V) MIN. @IT	BREAKDOWN VOLTAGE VBR (V) MAX. @IT	TEST CURRENT IT (mA)	MAXIMUM CLAMPING VOLTAGE @I _{PP} VC (V)	PEAK PULSE CURRENT I _{PP} (A)	REVERSE LEAKAGE @VRWM IR (uA)
SA70C	70.00	77.80	95.10	1	125.0	4.0	3
SA70CA	70.00	77.80	86.00	1	113.0	4.4	3
SA75C	75.00	83.30	102.00	1	134.0	3.7	3
SA75CA	75.00	83.30	92.10	1	121.0	4.1	3
SA78C	78.00	86.70	106.00	1	139.0	3.6	3
SA78CA	78.00	86.70	95.80	1	126.0	4.0	3
SA85C	85.00	94.40	115.00	1	151.0	3.3	3
SA85CA	85.00	94.40	104.00	1	137.0	3.6	3
SA90C	90.00	100.00	122.00	1	160.0	3.1	3
SA90CA	90.00	100.00	111.00	1	146.0	3.4	3
SA100C	100.00	111.00	136.00	1	179.0	2.8	3
SA100CA	100.00	111.00	123.00	1	162.0	3.1	3
SA110C	110.00	122.00	149.00	1	196.0	2.6	3
SA110CA	110.00	122.00	135.00	1	177.0	2.8	3
SA120C	120.00	133.00	163.00	1	214.0	2.3	3
SA120CA	120.00	133.00	147.00	1	193.0	2.0	3
SA130C	130.00	144.00	176.00	1	231.0	2.2	3
SA130CA	130.00	144.00	159.00	1	209.0	2.4	3
SA150C	150.00	167.00	204.00	1	269.0	1.9	3
SA150CA	150.00	167.00	185.00	1	243.0	2.1	3
SA160C	160.00	178.00	218.00	1	287.0	1.7	3
SA160CA	160.00	178.00	197.00	1	259.0	1.9	3
SA170C	170.00	189.00	231.00	1	304.0	1.6	3
SA170CA	170.00	189.00	209.00	1	275.0	1.8	3