

# Accutec Microcircuit Corporation

## AK5361024BW 1,048,576 Word by 36 Bit CMOS Dynamic Random Access Memory

### DESCRIPTION


The Accutec AK5361024BW high density memory module is a CMOS dynamic RAM organized in 1024K x 36 bit words. The module consists of two standard 1 Meg x 16 bits DRAMs and one 1 Meg x 4 bit Quad CAS DRAM in plastic SOJ packages. The assembly has 3 DRAMs mounted on the front side of a printed circuit board in a 72 pad leadless SIM configuration.

This configuration allows socket-mounting of large quantities of memory in applications where high density and ease of inserting additional memory are important.

The operation of the AK5361024BW is identical to eight 1 Meg x 4 plus four 1 Meg x 1 DRAMs. There are four  $\overline{\text{CAS}}$  lines and two  $\overline{\text{RAS}}$  lines. Independent byte control is accomplished by four  $\overline{\text{CAS}}$  lines. Each separate  $\overline{\text{CAS}}$  line controls one byte of the 1 Meg x 16 plus a parity bit in the QUAD CAS DRAM.

### FEATURES

- 1,048,576 x 36 bit organization
- 72 pad Single In-Line Module
- Standard with gold fingers, solder or tin plating optional
- $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ ,  $\overline{\text{RAS}}$ -only or hidden refresh
- Operating free air temperature 0°C to 70°C
- Single 5 Volt Power Supply
- 1024 Refresh Cycles, 16 mSEC
- Available in Fast Page Mode or EDO



- Power:
  - 2.125 Watt Max Active (50nS)
  - 1.975 Watt Max Active (60 nS)
  - 1.825 Watt Max Active (70 nS)
  - 30 mW Max Standby
- Downward compatible with AK536512W and AK536256W
- Upward compatible with AK5362048W, AK5364096W and AK5368192W

### ADDITIONAL OPTIONS AVAILABLE

- 1 Meg x 32 version, AK5321024BW
- 2 Meg x 32 version, AK5322048BW
- 2 Meg x 36 version, AK5362048BW

### PIN NOMENCLATURE

A <sub>0</sub> - A <sub>9</sub>	Address Inputs
DQ <sub>0</sub> - DQ <sub>35</sub>	Data In/Data Out
$\overline{\text{W}}$	Write Enable
$\overline{\text{RAS}}_0, \overline{\text{RAS}}_2$	Row Address Strobe
$\overline{\text{CAS}}_0 - \overline{\text{CAS}}_3$	Column Address Strobe
PD <sub>1</sub> - PD <sub>4</sub>	Presence Detect
Vss	Ground
Vcc	5v Supply
NC	No Connect

### MODULE OPTIONS

Leadless SIM: AK5361024BW


### PIN ASSIGNMENT

PIN #	SYMBOL	PIN #	SYMBOL	PIN #	SYMBOL	PIN #	SYMBOL
1	Vss	19	NC	37	DQ17	55	DQ12
2	DQ0	20	DQ4	38	DQ35	56	DQ30
3	DQ18	21	DQ22	39	Vss	57	DQ13
4	DQ1	22	DQ5	40	$\overline{\text{CAS}}_0$	58	DQ31
5	DQ19	23	DQ23	41	$\overline{\text{CAS}}_2$	59	Vcc
6	DQ2	24	DQ6	42	$\overline{\text{CAS}}_3$	60	DQ32
7	DQ20	25	DQ24	43	$\overline{\text{CAS}}_1$	61	DQ14
8	DQ3	26	DQ7	44	$\overline{\text{RAS}}_0$	62	DQ33
9	DQ21	27	DQ25	45	NC	63	DQ15
10	Vcc	28	A7	46	NC	64	DQ34
11	NC	29	NC	47	W	65	DQ16
12	A0	30	Vcc	48	NC	66	NC
13	A1	31	A8	49	DQ9	67	PD1
14	A2	32	A9	50	DQ27	68	PD2
15	A3	33	NC	51	DQ10	69	PD3
16	A4	34	$\overline{\text{RAS}}_2$	52	DQ28	70	PD4
17	A5	35	DQ26	53	DQ11	71	NC
18	A6	36	DQ8	54	DQ29	72	Vss


#### Presence Detect

	-50	-60	-70
PD1	Vss	Vss	Vss
PD2	Vss	Vss	Vss
PD3	Vss	NC	Vss
PD4	Vss	NC	NC

## FUNCTIONAL DIAGRAM



## MECHANICAL DIMENSIONS



**ACCUTEK MICROCIRCUIT CORPORATION**  
 BUSINESS CENTER at NEWBURYPORT  
 2 NEW PASTURE ROAD, SUITE 1  
 NEWBURYPORT, MA 01950-4054  
 VOICE: 978-465-6200 FAX: 978-462-3396  
 Email: sales@accutekmicro.com  
 Internet: www.accutekmicro.com

Accutek reserves the right to make changes in specifications at any time and without notice. Accutek does not assume any responsibility for the use of any circuitry described; no circuit patent licenses are implied. Preliminary data sheets contain minimum and maximum limits based upon design objectives, which are subject to change upon full characterization over the specific operating conditions.