




FR101 THRU FR107

FAST RECOVERY RECTIFIER
Reverse Voltage - 50 to 1000 Volts
Forward Current - 1.0 Ampere

Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Fast switching for high efficiency
- Construction utilizes void-free molded plastic technique
- 1.0 ampere operation at $T_A=55^\circ\text{C}$ with no thermal runaway
- High temperature soldering guaranteed: $250^\circ\text{C}/10$ seconds, 0.375"(9.5mm) lead length, 5 lbs. (2.3kg) tension

DO-41



Mechanical Data

- **Case:** DO-41 molded plastic body
- **Terminals:** Plated axial leads, solderable per MIL-STD-750, method 2026
- **Polarity:** Color band denotes cathode end
- **Mounting Position:** Any
- **Weight:** 0.012 ounce, 0.33 gram

DIMENSIONS					
DIM	inches		mm		Note
	Min.	Max.	Min.	Max.	
A	0.165	0.205	4.2	5.2	
B	0.079	0.106	2.0	2.7	φ
C	0.028	0.034	0.71	0.86	φ
D	1.000	-	25.40	-	

Maximum Ratings and Electrical Characteristics @25°C unless otherwise specified


	Symbols	FR 101	FR 102	FR 103	FR 104	FR 105	FR 106	FR 107	FR 107 -STR	Units
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	200	400	600	800	1000	1000	Volts
Maximum RMS voltage	V _{RMS}	35	70	140	280	420	560	700	700	Volts
Maximum DC blocking voltage	V _{DC}	50	100	200	400	600	800	1000	1000	Volts
Average forward rectified current at T _A =55℃	I _(AV)	1.0								Amp
Peak forward surge current 8.3mS single half sine-wave	I _{FSM}	30.0								Amps
Maximum instantaneous forward voltage I _{FM} =1.0A, T _A =25 (Note 3)	V _F	1.3								Volts
Maximum DC reverse current at rated DC blocking voltage T _A =25℃ T _A =100℃	I _R	5.0 100.0								μ A
Maximum reverse recovery time (Note 1)	T _{rr}	150				250	500		250	nS
Typical junction capacitance (Note 2)	C _J	15.0								ρ F
Operating and Storage temperature range	T _J , T _{STG}	-65 to +175								℃

Notes:

- (1) Reverse recovery test conditions: $I_F=0.5A$, $I_R=1.0A$, $I_{rr}=0.25A$
- (2) Measured at 1.0MHz and applied reverse voltage of 4.0 volts
- (3) Pulse test: pulse width 300uSec, Duty cycle 1%


RATINGS AND CHARACTERISTIC CURVES

Figure 1
Typical Forward Characteristics




Instantaneous Forward Current - Amperes *versus*
Instantaneous Forward Voltage - Volts

Figure 2
Forward Derating Curve



Average Forward Rectified Current - Amperes *versus*
Ambient Temperature - °C

Figure 3
Junction Capacitance



Junction Capacitance - pF *versus*
Reverse Voltage - Volts

RATINGS AND CHARACTERISTIC CURVES




Figure 5
Reverse Recovery Time Characteristic And Test Circuit Diagram

