


MODULAR CONNECTORS


CL 222 TM

EMI-proof right angle dip type connectors




(standard)
TM11R-5L-88
CL222-2667-3


(With ferrite core)
TM11R-5LF-88
CL222-2668-6



View of mating plug
A-A





**Reference mounting dimensions
(PCB component side) —**



Note: When preparing frames or PCBs, provide the above for the connector.


EMI-proof quadruplet right angle dip type connectors




(Standard)
TM11R-5L-3232
CL222-2720-4

(With ferrite core)
TM11R-5LF-3232
CL222-2722-0


View of mating plug
A-A



Reference mounting dimensions (PCB component side)



No pattern is allowed in this area

Note: When preparing frames or PCBs, provide the above  for the connector.
No pattern is allowed in the hatched area(s) on the connector side of the boards.

EMI-PROTECTED JACKS

● GENERAL

The EMI-protected modular connectors have been developed from the TM Series connectors, to resist noise. Designed to comply with the FCC (Federal Communications Commission) 68 Standard, they range from standard parts to EMI-protected parts.

Furthermore, they are highly operable and resistant to severe environmental conditions to ensure customer satisfaction with shielding performance.

● FEATURES



- (1) Plug connectors have a single-body shell and clamp to ensure secure protection from EMI.
- (2) To prevent electrostatic problems, plug connectors are designed so that the metal shell can be covered with a plastic hood.
- (3) Jack connectors that allow the shielded parts to be connected first during mating to protect the circuits within the set.
- (4) Plug harnesses can be wired easily and securely with a special tool.
- (5) Eight-conductor plugs and jack connectors comply with the ISO 8877 Standard (ISDN interface connector).

● MAIN APPLICATIONS


ISDN related equipment, HBS, mobile telephones, office automation equipment.

● JACKS WITH LEAD WIRES

● TM IIR-88-35S-300 CL222-1389-7




Standard color arrangement



Note: Standard finish color is grey.

Reference mounting drawing





MODULAR CONNECTORS


Right angle dip type connectors

CL 222 TM



● TM11R-5C-66 CL222-2148-6




Board mounting dimensional drawing (connector side)



● TM11R-5C-88 CL222-1378-0





Board mounting dimensional drawing (connector side)



Note: Cover standard color is black.

Right angle dip type connectors (With a decorative panel)

● TM11R-5E1-88
CL222-3820-4



Straight dip type connectors

● TM11R-3C-88
CL222-2133-9

